

MODEL DL-1

DATA LOGGER
4 CHANNELS



Easy to Use Software

(included)



FEATURES:

- 4 Channels, Independent Grounds
- 1,000/sec. to Once Every 99 Minutes
- 1,000,000 Sample Memory
- USB Communication
- Easy to Use Software (included)



Distributed by:

teststations.com

detectron.com

Info@tinker-rasor.com | tinker-rasor.com

INKER & RASOR

PRODUCT DATA SHEET | MODEL DL-1 DATA LOGGER

FEATURES:

- Completely redesigned
- 1 million read memory
- Configure Sample frequency anywhere from 1000 reads per second to 1 read every 99 minutes
- 4 Channels with independent grounds
- 2 DC Channels with AC filtering, +/- 5 volts
- 1 AC Channel, 150 volts RMS
- TrueView Channel with no filtering, +/-100 volts
- 200+ MegW Impedance/Channel
- USB Connection to PC
- Several status LEDs on instrument
- New instrument case

APPLICATIONS:

- Interference testing
- Pipe to Soil measurements
- Anode output reads
- CIS verification
- Telluric events
- Stray currents

SOFTWARE:

- TRAC4 software program included
- Available for download from T&R website
- Configuration and setup notes saves in all data files
- Shunt configuration shows current in data and graph
- Easy to use, single click graphing
- Exportable to other common programs

ENVIRONMENT:

Operating Temp. Range --10°C to 60°C (14°F to 140°F)

Storage Temp. Range --20°C to 70°C (-4°F to 158°F)

SPECIFICATIONS:

Rechargeable Li-Ion battery 4 TRAC Software (included and downloadable)

DIMENSIONS:

INSTRUMENT: 10.75" x 1.5" x 1.5", 0.5 lbs. (273mm x 38mm x 38mm, 0.227kg)

CARRYING CASE: 12" x 6.75" x 4.5", 2 lbs. (305mm x 171mm x 114mm, 0.908kg)

SHIPPING DIMENSIONS:

13" x 7.5" x 5", 4 lbs. (330mm x 191mm x 127mm, 1.81kg)



AVAILABLE FROM STOCK

tinker-rasor.com

DELIVERY: Immediately from STOCK

F.O.B. New Braunfels, TX USA

SERVICE: 24-hour Turn-Around

TERMS: Net 30 Days, on approval of credit

WARRANTY: 90 Days, parts and labor